

**PM2118**

AC/DC Digital Clamp Meter



DIGITAL CLAMP METERS



SPECIFICATIONS	RANGE	
DCV	600V	±(0.5%+3)
ACV(40~65Hz)	0.01~600V	±(0.8%+5)
Ω	0~60MΩ	±(0.8%+3)
Continuity	<30Ω	<30Ω
ACA(40~65Hz)	200mA~400A	±(2.5%+5)
	400A~600A	±(3%+5)
DCA	10mA~400A	±(3%+3)
	400A~600A	±(3.5%+3)
Capacitance	0.1uF~6000uF	±(3%+3)
Frequency	40Hz-1000Hz	
LowZ	1.0~600V	±(0.8%+3)
DCuA	0~200uA	±(0.8%+3)
°C/°F	-40~1000°C	±(1%+2)
	-40~1832°F	±(1%+2)
FEATURE		
Counts	6000	
RANGE	Auto	
ACA	60A/600A	
DCA	60A/600A	
DCV	6V/60V/600V	
ACA	6V/60V/600V	
Continuity	√	
Ω	6kΩ/60kΩ/600kΩ/6MΩ/60MΩ	
DCuA	√200uA	
Frequency(Clamp)	1KHz	
Frequency(Voltage)	1KHz	
°C/°F	√	
LPF(1kHz -3dB)	√	
LowZ	√	
Capacitance	600uF/6000uF	
Data Hold	√	
BackLight	√	
NCV	√	
Low Battery Indication	√	
Auto Power Off	√	
Dual Display	√	
GENERAL		
Power Supply	2 x 1.5V AAA Battery	
Weight	250g	
Size	189x70x37mm	
Jaw Size	ø 24mm	
Safety Rating	EN61010-1,EN61010-2-032, EN61326,CAT.III 600V	

