

## PM6252A/B

Digital Anemometer & Humidity & Temperature Meter

DIGITAL ANEMOMETERS



AIR VELOCITY	Range	Accuracy	
		PM6252A	PM6252B
m/s (meter per second)	0.40~30.0	±(2.0% + 50)	±(2.0% + 50)
ft/m (feet per minute)	80~5900	±(2.0% + 50)	±(2.0% + 50)
km/h (kilometer per hour)	1.4~108.0	±(2.0% + 50)	±(2.0% + 50)
mile/h(mile per hour)	0.9~67.0	±(2.0% + 50)	±(2.0% + 50)
Knots(nautical miles per hour)	0.8~58.0	±(2.0% + 50)	±(2.0% + 50)
Air Temperature	-20 to 60°C (-14 to 140°F)		1.5°C(±2.7°F)
Air Relative Humidity	0 to 100% RH		±3%
AIR FLOW	RANGE	AREA	
CFM	0 to 999990	0 to 9.999ft <sup>2</sup>	
CMM	0 to 999990	0 to 9.999m <sup>2</sup>	
CMS	0 to 99999	0 - 9.999 m <sup>2</sup>	
General			
	PM6252A	PM6252B	
Flow Area Setting	✓	✓	
MAX/MIN Function	✓	✓	
Display Back light	✓	✓	
Auto Power Off	✓	✓	
° C/°F Selection		✓	
Ambient , Dew Point & Wet Bulb Temperature		✓	
Low Battery indication	✓	✓	
USB Interface		✓	
Power Supply	1 x 9 V 6 F 22		
Product Size	170x86x39mm		
Product Weight	Approx. 200g		
Category	EN61010-1, EN61326-1		

